

PRODUCT NAME

Satin Trim Paint

ORIGINALLY ISSUED

08/08/2017

VERSION

1.0

PRODUCT CODE

DEC702

VERSION DATE

08/08/2017



PRODUCT DESCRIPTION

A high quality, mid sheen satin decorative and protective finish for interior and exterior use over correctly prepared joinery. Ideal for windows, doors, soffits and fascias.



IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. HMG will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use
- If in any doubt speak HMG Technical Service Department on (0161) 205 7631



MAXIMUM VOC CONTENT (RFU)

0.11Kg/L

REGULATIONS / COMPLIANCE

- 2004/42 IIA WB (D) 130



COLOUR RANGE

- Special colours can be matched by request
- White



GENERAL INFORMATION

Coverage	12 square metres per litre @ 30 microns dft
Flashpoint	X°C
Storage	Store between 5°C - 25°C. When not in use, cans must be kept sealed
Shelf Life	12 months from delivery date in original sealed containers



CLEANING

Ensure surfaces to be coated are dry and must be cleaned using the appropriate HMG product to remove all traces of contaminants.

HMG produce a full range of cleaners, silicone removers, degreasers and preparatory cleaners suitable for the cleaning process.

Please refer to our website for Knowledge Base article Prep-Cleaning Techniques (KNB0009) and Preparatory Cleaners from the Product Guide.



SURFACE PREPARATION

Please refer to Knowledge Base for details on Surface Preparation.



HEALTH AND SAFETY

- Refer to SDS and tin label prior to use.

APPLICATION METHODS



	BRUSH	ROLLER	COMPLIANT SPRAY GUN		
MIXING RATIO					
RFU		RFU	Base Thinner	5ltr >10%	
THINNER OPTIONS			Water	Water	
VISCOSITY	As supplied	As supplied	As supplied	As supplied	
NUMBER OF COATS (GUIDE ONLY)					
1-2 Coats		1-2 Coats	1-2 Coats		
FLASH OFF					
DRYING TIME					
Touch dry	30mins @20°C	Touch dry	30mins @20°C	Touch dry	30mins @20°C
Hard dry	24 hours	Hard dry	24 hours	Hard dry	24 hours
RECOATABILITY / OVERCOATING	4-6hrs dependant on wft and drying conditions e.g. temp and air movement. If not fully ready, dragging and film damage may occur.				
WET FILM THICKNESS*					
80microns		80microns		80microns	



	DRY FILM THICKNESS*		
30microns	30microns	30microns	

* - HMG Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the dft stated in the agreed specification and to avoid areas of excessively low or high thickness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of HMG's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. For professional use only.