

PRODUCT NAME

Polyurethane Floor Paint

ORIGINALLY ISSUED

22/09/2005

VERSION

1.0

PRODUCT CODE

TOPFLOOR

VERSION DATE

22/09/2005



PRODUCT DESCRIPTION

Polyurethane Floor Paint has been designed to provide a hard wearing yet economical surface coating.

Its durability is achieved by the use of excellent quality resins, which also provide the user with a product that is very easy to use.



IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. HMG will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use
- If in any doubt speak HMG Technical Service Department on (0161) 205 7631



MAXIMUM VOC CONTENT (RFU)

0.450Kg/L

REGULATIONS / COMPLIANCE

- 2004/42 IIA SB (I) 500



COLOUR RANGE

- Available in a wide colour range including RAL & BS shades



GENERAL INFORMATION

Coverage 10 square metres per litre
Flashpoint 31°C
Storage Store between 5°C - 25°C. When not in use, cans must be kept sealed
Shelf Life 12 months from delivery date in original sealed containers



CLEANING

Ensure surfaces to be coated are dry and must be cleaned using the appropriate HMG product to remove all traces of contaminants.

HMG produce a full range of cleaners, silicone removers, degreasers and preparatory cleaners suitable for the cleaning process.

Please refer to our website for Knowledge Base article Prep-Cleaning Techniques (KNB0009) and Preparatory Cleaners from the Product Guide.



SURFACE PREPARATION

Please refer to Knowledge Base for details on Surface Preparation.



SUGGESTED PRIMER / FILLER / SEALER SYSTEMS

- HMG Concrete Sealer



HEALTH AND SAFETY

- Refer to SDS and tin label prior to use.

APPLICATION METHODS



MIXING RATIO

BRUSH		ROLLER	
RFU		RFU	



NUMBER OF COATS (GUIDE ONLY)

1-2 coats	1-2 coats
-----------	-----------



DRYING TIME

Touch dry	2hrs@20°C	Touch dry	2hrs@20°C
Hard dry	4-6hrs@20°C	Hard dry	4-6hrs@20°C
Full dry	24hrs@20°C	Full dry	24hrs@20°C



RECOATABILITY / OVERCOATING

After 8hrs @ 20°C