

PRODUCT NAME

Vinyl Silk Emulsion

ORIGINALLY ISSUED

10/09/2015

VERSION

1.0

PRODUCT CODE

DEC201

VERSION DATE

10/09/2015



PRODUCT DESCRIPTION

A premium quality water-based, silk emulsion for interior use on wall and ceiling surfaces, where a washable high sheen finish is required.



IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. HMG will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use
- If in any doubt speak HMG Technical Service Department on (0161) 205 7631



MAXIMUM VOC CONTENT (RFU)

0.005Kg/L

REGULATIONS / COMPLIANCE

- 2004/42 IIA WB (A) 30



COLOUR RANGE

- White
- Essentials Colour Collection
- Special colours can be matched by request



PACKAGING

5 & 10 litres



GENERAL INFORMATION

Coverage	Up to 16 sq m on smooth surfaces
Flashpoint	> 100°C
Temp Resistance	n/a°C
Storage	Store between 5°C - 25°C. When not in use, cans must be kept sealed
Shelf Life	12 months from delivery date in original sealed containers



CLEANING

Ensure surfaces to be coated are dry and must be cleaned using the appropriate HMG product to remove all traces of contaminants.

HMG produce a full range of cleaners, silicone removers, degreasers and preparatory cleaners suitable for the cleaning process.

Please refer to our website for Knowledge Base article Prep-Cleaning Techniques (KNB0009) and Preparatory Cleaners from the Product Guide.



SURFACE PREPARATION

Please refer to Knowledge Base on our website for details on Surface Preparation.



ADDITIONAL INFORMATION

Waterbased
Tough washable finish
Quick drying
Good opacity
Easy application



HEALTH AND SAFETY

- Refer to SDS and tin label prior to use.

APPLICATION METHODS



MIXING RATIO

BRUSH		ROLLER	
RFU		RFU	



HARDENER OPTIONS

--	--	--	--







THINNER OPTIONS

		water	water
--	--	-------	-------



NUMBER OF COATS (GUIDE ONLY)

1-2 coats	1-2 coats		
-----------	-----------	--	--

	DRYING TIME						
	Touch dry Hard dry	1 hr @ 20°C 24 hours @ 20°C	Touch dry Hard dry	1 hr @ 20°C 24 hours @ 20°C			
	RECOATABILITY / OVERCOATING						
	4 hrs minimum		4 hrs minimum				
	WET FILM THICKNESS*						
	65 microns		65 microns				
	DRY FILM THICKNESS*						
	25 microns		25 microns				
<p><small>* - HMG Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the dft stated in the agreed specification and to avoid areas of excessively low or high thickness.</small></p>							

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of HMG's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. For professional use only.